



Y4000 – All-In-One POS Platform

The new Y series, Y4000 dual-screen integrated POS cash register

- 13.3-inch main display TouchPro PCAP touchscreen HD display supports up to 10-point multi-touch response
- 10.1 inch customer display Bright display, better customer experience
- 3-inch receipt printer with automatic cutter, supports 80x60mm (width x diameter) roll paper; compatible with 58mm (2-inch) paper roll printing, suitable for different scenarios
- Aluminium cash drawer, consumer-grade craftsmanship, smooth and matte visual contrast, simple & restrained, showing quality. Comes with 3 bills, 4 coins, mechanical lock key.



ARM Cortex-A53 2.0GHz



Android 11



32GB + 3GB DDRX



Wi-Fi, Ethernet



Customer Display



Pay Scan Code



Printer



Cash Drawer



Compassion. Innovation. Trust.

Y4000 Tech Specs



What's in the Box

YC4000 (includes cash drawer, printer, 2D barcode scanner, customer facing display), power cable, 1 receipt paper rolls, 2 cash drawer keys, Quick Install Guide, 1 RJ50 to DB9 cable, power adapter

OS

Android 11

Processor

4xARM Cortex-A53 up to 2.0GHz

Memory

RAM : 3GB DDR4X
ROM : 32GB

Printer

80mm 3" printer with automatic cutter, supports 80x60mm roll paper; compatible with 58mm (2") roll paper

Display

Main Display :
13.3" diagonal, Active matrix TFT LCD (LED), 16x9, Full HD 1920 x 1080 @ 60H, Touch Technology: PCAP (TouchPro® Projected Capacitive) - 10-point touch, With CTP: 200 nits

Customer Facing Display :
10.1" non touch, 16x9
1280*800

Wireless

IEEE 802.11
a/b/g/n/ac, 2.4G&5G;
Bluetooth: 5.0

Ports

I/O ports : 4 x Type A USB 2.0, 1 x micro USB for debug, 1 x RJ50 serial with 5V power , DC jack x 1
Ethernet port : 1 x LAN (100M)

Cash Drawer

Removable till insert,
3 position lock, 3 bill trays,
4 coin compartments

Barcode Scanner

0.3MP QR code scanner
(on the second display to scanner the QR code from customer)

Speakers

2 x 1W internal speakers

Color

*White/
Black

Dimensions

12.6" x 13.0" x 9.6" /
320mm x 330mm x
243mm

Weight

Unpackaged:
14.99 lbs / 6.8 kg;
Packaged:
18.52 lbs / 8.4 kg

Power Supply

External power supply:
AC input voltage:
100-240 VAC;
Input frequency:
50-60 Hz

Temperature

Operating: 32°F to 95°F (0°C to 35°C);
Storage -4°F to 140°F (-20°C to 60°C)
Humidity (non-condensing) :
Operating: 20% to 80%;
Storage: 5% to 95%

Regulatory Approvals and Declarations CCC, SRRC, China RoHS

1. The usable memory may be less than the installed memory.
2. All specifications are subject to change without (prior) notice.