Y2000 -Android POS Terminal

Professional all-powerful design to redefine industrial payment

- High-performance quad-core processor
- Industrial high-strength 5″ large display - 720P HD resolution rate, Android 8.1 OS
- Professional code scan engine, Quick printing, Highly optimized power system, Flexible communication
- Make payments with the palm of your hand

Optional Accessories

Contactless Card

IC Card

MagStripe Card

QR Payment

Compassion. Innovation. Trust.

Y2000 Tech Specs

CPU	OS	Memory	Display
Quad-Core 1.3GHz	Android 8.1	RAM: 2GB ROM: 16GB Micro SD/TFx1, up to 128 GB	5.0"display, 1280×720

Dimension	Power	Magcard	Chip Card
L x W x H (mm): 184 x 81 x 47 (32mm thinnest) Weight: 431g(without battery)	Rechargeable 3.8V, 5000mAh lithium polymer battery pack (Typical Operation time≥8 hours)	Support magnetic 1/2/3 track card, bidirectional swipe, and meet the standards of ISO7811/7812/7813 IC Card: Meet the standard of ISO/IEC 7816	Meet the standard of ISO/IEC 7816

Contactless Card	Printing	Scanning	Camera
Support Mifare, type A/B/C , Felica	Media type: Receipt paper, Media roll size: 30mm, Media width: 58mm printing paper, Resolution: 203dpi (8dot/mm) Print speed: 50mm/s, Supports 1D/2D bar code printing	Rear camera decoding 2D scan engine (optional)	Rear 5MP AF

Notification LED	Adaptor	Interface	Network Connection
Contactless Notification LED, Blue/ Yellow/ Green/ Red Power LED	Input: 100~240V AC 50~60Hz Output: 5V/2A	Micro USB (data transferring and charging, USB OTG 2.0) DC Jack (charging) 3.5mm audio jack Pogopin (8pin)	FDD-LTE, TDD-LTE, WCDMA, CDMA 2000, CDMA, GSM/EDGE/GPRS Bluetooth: BT 4.1+BR/EDR/BLE Wi-Fi (2.4GHz/ 5GHz)

GPS	Buttons	Certification	Environment parameter
GPS, A-GPS, BEIDOU, GL ONASS	Volume +/- key, power key , scan key x2, custom key Fn key, cancel key, delete key, enter key.	CE, FCC, RoHS, PCI, EMV LEVEL 1&2certificated, EVM contactless LEVEL 1 certificated, PayWave, PayPass, American Express Expresspay certificated etc.	Operating: -10℃~50℃ Storage: -20℃ ~ 70℃ Humidity: 5%RH ~ 95%RH (No condensation) Drop resistance: multiple 1.3m drops to concrete

* Please note that this introduction will be adjusted with the product updates, and the information is subject to change without prior notice.